

Material: AFNOR NF A 420 C-M

Standard Specification for Steel Casting and Nickel Alloy Castings for Pump, Valve and Fitting

Group: Ferrous Mild Steel Alloys

Sub Group: AFNOR NF A 420 C-M Steel Casting and Nickel Alloy Castings for Pump, Valve and Fitting

Application: Intended for Valve, Pump, General Engineering, Automotive and Other Industries

Grade Belongs to the Industry: Pump, Valve and Fitting

Chemical Composition			Heat Treatment	
Carbon	C %	0.230 max.	Normalizing or Quenching or Solution Annealing	
Silicon	Si %	0.600 max.		
Manganese	Mn %	1.000 max.		
Phosphorus	P %	0.030 max.		
Sulphur	S %	0.030 max.		
Iron	Fe %	Balance		
-	-	-		
-	-	-		
-	-	-		
-	-	-		
			Mechanical Properties	
			Tensile Strength in Mpa	420 min.
			Yield Strength in Mpa	240 min.
			Elongation in %	25 min.
			Reduction of Area in %	-
			Hardness in HB	130 - 165
			Impact in Joule	24 J @ RT

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
EN 10213 GP240GH	BS	British	Plate, Tubes and Forging
A 216 Grade WCB	ASTM	USA	Casting
A 420 M	AFNOR NF	France	Pump, Valve and Fitting
Ao 17 CrMoV	MSZ	Hungary	Plate, Tubes and Forging
SCPH 1	JIS	Japan	Plate, Tubes and Forging
GP 240 GH	UNE	Spain	Plate, Tubes and Forging
1.0619	EN	European Union	Plate, Tubes and Forging

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com