

Material: ASME SA-276 XM-27

Standard Specification for Stainless Steel Bars and Shapes

Group: Ferrous Stainless Steel Alloys

Sub Group: ASME SA-276 XM-27 Stainless Steel Bars and Shapes

Application: Intended for Valve, Pump, General Engineering, Automotive and Other Industries

Grade Belongs to the Industry: Bar and Shapes

Chemical Composition			Heat Treatment	
Carbon	C %	0.010 max.	Normalizing or Annealing or Hardening + Tempering	
Silicon	Si %	0.400 max.		
Manganese	Mn %	0.400 max.		
Phosphorus	P %	0.020 max.		
Sulphur	S %	0.020 max.		
Chromium	Cr %	25.000 - 27.500		
Molybdenum	Mo %	0.750 - 1.500		
Nickel	Ni %	0.500 max.		
Niobium	Nb %	0.050 - 0.200		
Nitrogen	N %	0.150 max.		
Ni+Cu	Ni% + Cu%	0.500 max.	Mechanical Properties	
Copper	Cu %	0.200 max.	Tensile Strength in Mpa	450 min.
Iron	Fe %	Balance	Yield Strength in Mpa	275 min.
-	-	-	Elongation in %	16 min.
-	-	-	Reduction of Area in %	45 min.
			Hardness in HB	219 max.
			Impact in Joule	-

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
A176 Type XM-27	ASTM	USA	Plate, Sheet and Strip
A240 Type XM-27	ASTM	USA	Plate, Sheet and Strip
A276 XM-27	ASTM	USA	Bar and Shapes
S44627	UNS	USA	Plate, Sheet and Strip
SM-27	SAE	USA	Plate, Sheet and Strip
SA-731 TPXM-27	ASME	USA	Casting
A731 TP XM-27	ASTM	USA	Casting

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com