

Material: ASME SB-283 C67600

Standard Specification for Copper and Copper-Alloy Die Forgings

Group: Non-Ferrous Copper Alloy

Sub Group: ASME SB-283 Copper and Copper-Alloy Die Forgings

Application: Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade

Belongs to the Industry: Forging

Chemical Composition			Heat Treatment	
Iron	Fe %	0.400 - 1.300	Normalizing or Annealing or Tempering	
Manganese	Mn %	0.050 - 0.500		
Lead	Pb %	0.500 - 1.000		
Tin	Sn %	0.500 - 1.500		
Copper	Cu %	57.000 - 60.000		
Zinc	Zn %	Balance		
-	-	-		
-	-	-	Mechanical Properties	
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-		
			Mechanical Properties	
			Tensile Strength in Mpa	495 min.
			Yield Strength in Mpa	235 min.
			Elongation in %	33 min.
			Reduction of Area in %	-
			Hardness in HRB	69 min.
			Impact in Joule	-

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
B124 C67600	ASTM	USA	Rod, Bar and Shapes
B138 C67600	ASTM	USA	Rod, Bar and Shape
B283 C67600	ASTM	USA	Forging
C67600	UNS	USA	Rod, Bar and Shape
-	-	-	-
-	-	-	-
-	-	-	-

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com