

Material: ASTM A 954 S70003

Standard Specification for Austenitic Chromium-Nickel-Silicon Alloy Steel Seamless and Pipe

Group: Non-Ferrous Nickel Alloys

Sub Group: ASTM A 954 S70003 Austenitic Chromium-Nickel-Silicon Alloy Steel Seamless and Pipe

Application: Intended for Valve, Pump, General Engineering, Automotive and other Industries

Grade Belongs to the Industry: Pipe

Chemical Composition			Heat Treatment	
Carbon	C %	0.020 max.	As-Cast or Annealing or Age Hardning	
Silicon	Si %	6.500 - 8.000		
Manganese	Mn %	2.000 max.		
Chromium	Cr %	8.000 - 11.000		
Sulphur	S %	0.010 max.		
Molybdenum	Mo %	0.500 max.		
Phosphorus	P %	0.025 max.		
Nickel	Ni %	22.000 - 25.000		
-	-	-	Mechanical Properties	
-	-	-	Tensile Strength in Mpa	540 min.
-	-	-	Yield Strength in Mpa	240 min.
-	-	-	Elongation in %	40 min.
-	-	-	Reduction of Area in %	-
-	-	-	Hardness in BHN	-
-	-	-	Impact in Joule	-

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
A 946 Grade S70003	ASTM	USA	Plate, Sheet and Strip
A 953 S70003	ASTM	USA	Tube
A 968 S70003	ASTM	USA	Bars and Shapes
1.439	DIN	Germany	Plate, Sheet and Strip
X 1 NiCrSi 24-9-7	DIN	Germany	Plate, Sheet and Strip
S70003	UNS	USA	Plate, Sheet and Strip
-	-	-	-

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com