

Material: ASTM B283 C62300

Standard Specification for Copper and Copper-Alloy Die Forgings

Group: Non-Ferrous Copper Alloy

Sub Group: ASTM B283 Copper and Copper-Alloy Die Forgings

Application: Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade

Belongs to the Industry: Forging

Chemical Composition		
Aluminium	Al %	8.500 - 10.000
Iron	Fe %	2.000 - 4.000
Manganese	Mn %	0.500 max.
Ni + Co	Ni% + Co%	1.000 max.
Silicon	Si %	0.250 max.
Tin	Sn %	0.600 max.
Copper	Cu %	Balance
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

Heat Treatment
Normalizing or Annealing or Tempering

Mechanical Properties	
Tensile Strength in Mpa	565 min.
Yield Strength in Mpa	255 min.
Elongation in %	32 min.
Reduction of Area in %	-
Hardness in HRB	82 min.
Impact in Joule	-

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
B124 C62300	ASTM	USA	Rod, Bar and Shapes
B150 C62300	ASTM	USA	Rod, Bar and Shape
SB-150 C62300	ASME	USA	Rod, Bar and Shape
SB-283 C62300	ASME	USA	Forging
C62300	UNS	USA	Rod, Bar and Shape
C62300	AS	Australia	Ingot and Casting
-	-	-	-

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 **Email:** info@icastllp.com



+91-99090 45075



info@icastllp.com



ICAST ALLOYS LLP, Plot 2527, Road H1, Kranti Gate, GIDC Metoda, Lodhika, Rajkot-360021, Gujarat, India