

Material: ASTM B472 N06022

Standard Specification for Nickel and Nickel-Related Alloy Wire

Group: Non-Ferrous Nickel Alloys

Sub Group: ASTM B472 N06022 Nickel and Nickel-Related Alloy Wire

Application: Intended for Valve, Pump, General Engineering, Automotive and other Industries

Grade Belongs to the Industry: Wire

Chemical Composition		
Carbon	C %	0.015 max.
Chromium	Cr %	20.000 - 22.500
Cobalt	Co %	2.500 max.
Iron	Fe %	2.000 - 6.000
Manganese	Mn %	0.500 max.
Molybdenum	Mo %	12.500 - 14.500
Phosphorus	P %	0.020 max.
Sulphur	S %	0.020 max.
Silicon	Si %	0.080 max.
Vanadium	V %	0.350 max.
Tungsten	W %	2.500 - 3.500
Nickel	Ni %	Balance
-	-	-
-	-	-
-	-	-

Heat Treatment
As-Cast or Annealing or Age Hardning

Mechanical Properties	
Tensile Strength in Mpa	765 - 1700
Yield Strength in Mpa	359 - 407
Elongation in %	57 - 70
Reduction of Area in %	-
Hardness in HRC	84 - 88
Impact in Joule	-

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
Hastelloy C22	Gravity	India	Wire
N06022	UNS	USA	Wire
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com



+91-99090 45075



info@icastllp.com



ICAST ALLOYS LLP, Plot 2527, Road H1, Kranti Gate, GIDC Metoda, Lodhika, Rajkot-360021, Gujarat, India