

Material: BS 1490 LM30

Standard Specification for Aluminium and Aluminium Alloy Ingots and Casting for General Engineering Purpose

Group: Non-Ferrous Aluminium Alloy

Sub Group: Aluminium Alloy BS 1490 for Ingots and Casting General Engineering Purpose

Application: Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade

Belongs to the Industry: Ingot and Casting

Chemical Composition			Heat Treatment	
Copper	Cu %	4.000 - 5.000	As-Cast	
Magnesium	Mg %	0.400 - 0.700		
Silicon	Si %	16.000 - 18.000		
Iron	Fe %	1.100 max.		
Manganese	Mn %	0.300 max.		
Nickel	Ni %	0.100 max.		
Zinc	Zn %	0.200 max.		
Lead	Pb %	0.100 max.		
Tin	Sn %	0.100 max.		
Titanium	Ti %	0.200 max.		
Other	Ot%	0.300 max.		
Aluminium	Al %	Balance		
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-		

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
ADC 14	JIS	Japan	Casting
390.0	AA	USA	Casting
AC-48100	EN	European Union	Casting
EN AC-48100	DIN	Germany	Casting
AlSi17Cu4Mg	ISO	International	Casting
ALDC 14	KS	Korea	Casting
EN AC-48100	UNE	Spain	Casting

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com