

Material: IS 6912 7% Al Bronze FAB1

Standard Specification for Copper and Copper Alloy Forging Stock and Forgings

Group: Non-Ferrous Copper Alloy

Sub Group: IS 6912 Copper and Copper Alloy Forging Stock and Forgings

Application: Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade

Belongs to the Industry: Forging

Chemical Composition		
Lead	Pb %	0.050 max.
Tin	Sn %	0.100 max.
Manganese	Mn %	0.500 max.
Magnesium	Mg %	0.050 max.
Nickel	Ni %	0.500 max.
Iron	Fe %	2.000 - 3.500
Silicon	Si %	0.150 max.
Zinc	Zn %	0.400 max.
Other	Ot%	0.500 max.
Aluminium	Al %	6.500 - 8.000
Copper	Cu %	Balance
-	-	-
-	-	-
-	-	-
-	-	-

Heat Treatment
As Raw

Mechanical Properties	
Tensile Strength in Mpa	460 min.
Yield Strength in Mpa	-
Elongation in %	30 min.
Reduction of Area in %	-
Hardness in BHN	-
Impact in Joule	-

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 **Email:** info@icastllp.com



+91-99090 45075



info@icastllp.com



ICAST ALLOYS LLP, Plot 2527, Road H1, Kranti Gate, GIDC Metoda, Lodhika, Rajkot-360021, Gujarat, India