

Material: JIS H 5302 ADC12Z

Standard Specification for Aluminium Alloy Castings

Group: Non-Ferrous Aluminium Alloy

Sub Group: JIS H 5302 Aluminium Alloy Castings

Application: Intended for Valve, Pump, General Engineering, Automotive and Other Industries Grade

Belongs to the Industry: Ingot and Casting

Chemical Composition			Heat Treatment	
Copper	Cu %	1.500 - 3.500	As-Cast	
Iron	Fe %	1.300 max.		
Magnesium	Mg %	0.300 max.		
Manganese	Mn %	0.500 max.		
Nickel	Ni %	0.500 max.		
Lead	Pb %	0.200 max.		
Silicon	Si %	9.600 - 12.000		
Tin	Sn %	0.200 max.		
Zinc	Zn %	3.000 max.		
Aluminium	Al %	Balance		
-	-	-	Mechanical Properties Tensile Strength in Mpa - Yield Strength in Mpa - Elongation in % - Reduction of Area in % - Hardness in BHN - Impact in Joule -	
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-		
-	-	-		

Cross Reference Table			
Material	Standard	Country	Grade Belong to the Industry
AA307	AS	Australia	Ingot and Casting
307	AS	Australia	Ingot and Casting
4520	IS	India	Ingot and Casting
ADC12	JIS	Japan	Ingot and Casting
LM2	BS	British	Ingot and Casting
383	AA	USA	Ingot and Casting
-	-	-	-

Disclaimer: All information displayed in our data sheets are for reference purpose only and are sole property of their respective owners. Information and or material are used for educational purposes only. Data at actual may vary at actual and case to case basis. ICAST Alloys LLP does not guarantee validity of these parameters. Warranties and liabilities are exclusive to our terms and conditions of business.

Customer Care: +91-99090 45075 Email: info@icastllp.com